



SERVICE		COP
POWER	kVA	997
POWER	kW	997
RATED SPEED	r.p.m.	1.500
MAIN VOLTAGE	V	400/230
AVAILABLE VOLTAGES	V	200/115 230 V (t) 380/220 415/240
RATED AT POWER FACTOR	Cos Phi	1,0



INDUSTRIAL RANGE

HIMOINSA Company with quality certification ISO 9001

HIMOINSA gensets are compliant with EC mark which includes the following directives:

- 2006/42/CE Machinery safety.
- 2014/30/UE Electromagnetic compatibility.
- 2014/35/UE electrical equipment designed for use within certain voltage limits
- 2000/14/EC Sound Power level. Noise emissions outdoor equipment. (amended by 2005/88/EC)
- 97/68/EC Emissions of gaseous and particulate pollutants.
- EN 12100, EN 13857, EN 60204

Ambient conditions of reference according to ISO 8528-1:2020 normative: 1000 mbar, 25°C, 30% relative humidity.

Prime Power (PRP):

According to ISO 8528-1:2020, Prime power is the maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load when operated for an unlimited number of hours per year under the agreed operating conditions with the maintenance intervals and procedures being carried out as prescribed by the manufacturer. The permissible average power output (Ppp) over 24 h of operation shall not exceed 70 % of the PRP.

Continuous Power (COP): According to Standard ISO 8528-1:2020, this is the maximum power available for continuous loads for unlimited running hours a year between the maintenance times recommended by the manufacturer under the environmental conditions established by the same.

Class G2 performance according to the load impact test according to ISO 8528-5:2020

HIMOINSA HEADQUARTERS:

Fábrica: Ctra. Murcia - San Javier, Km. 23,6 | 30730 SAN JAVIER (Murcia) Spain
Tel.+34 968 19 11 28 Fax +34 968 19 12 17 Fax +34 968 19 04 20 |
info@himoinsa.com | www.himoinsa.com

Manufacture facilities:

SPAIN • FRANCE • INDIA • CHINA • USA • BRAZIL • ARGENTINA

Subsidiaries:

PORTUGAL | POLAND | GERMANY | UK | SINGAPORE | UAE | PANAMA |
DOMINICAN REPUBLIC | ARGENTINA | ANGOLA | SOUTH AFRICA | MOROCCO



OPEN SKID



OPEN SKID



WATER-COOLED



THREE PHASE



50 HZ



LPG

Himoinsa has the right to modify any feature without prior notice.

Weights and dimensions based on standard products. Illustrations may include optional equipment.

Technical data described in this catalogue correspond to the available information at the moment of printing.

The illustrations and images are indicative and may not coincide in their entirety with the product.

Industrial design under patent.



Engine Specifications | 1.500 r.p.m.

Rated Engine Output (COP)	kW	1030
Manufacturer	GUASCOR	
Model	G.56SM	
Engine Type	4-stroke Otto Cycle	
Injection Type	Carburization	
Aspiration Type	Turbocharged	
Number of cylinders and arrangement	16-V	
Bore and Stroke	mm	160 x 175
Displacement	L	56,3
Cooling System	Water + Antifreeze	
Lube Oil Specifications	SAE 40	
Compression Ratio	9,2	

Fuel Consumption 100% COP	kW	2683
Fuel Consumption 80 % COP	kW	2203
Fuel Consumption 75 % COP	kW	2048,7
Fuel Consumption 50 % COP	kW	1448,37
Fuel Consumption 25 % COP	kW	852,89
Lube oil consumption with full load	g/kWh	0,1
Total oil capacity	L	272
Heat dissipated by coolant	kW	892
Governor	Type	Electrical
Air Filter	Type	Semi-humid



- LPG-liquefied petrol gas engine
- 4-stroke cycle
- Water-cooled
- Radiator with pusher fan
- HTW sender
- LOP sender
- Electronic governor
- Hot parts protection
- Moving parts protection



Generator Specifications | STAMFORD

Manufacturer	STAMFORD	
Model	S7L1D.C4	
Poles	No.	4
Connection type (standard)	Star	
Mounting type	S-00 18"	
Insulation	H class	


Enclosure (according IEC-34-5)	IP23
Voltage regulator	A.V.R. (Electronic)
Bracket type	Double drive-shaft
Coupling system	Elastic Coupling
Coating type	Standard (Vacuum impregnation)



- Self-excited and self-regulated
- 4 poles
- IP23 protection
- H class insulation
- Double drive-shaft

WEIGHT AND DIMENSIONS

Standard Version		
Length (L)	mm	Ask
Height (H)	mm	Ask
Width (W)	mm	Ask
Weight with liquids in radiator and sump		Ask
Autonomy (75%)	Hours	Ask



APPLICATION DATA

EXHAUST SYSTEM

Maximum exhaust temperature	°C	470
Exhaust Gas Flow	kg/s	1,4
Maximum allowed back pressure	mm H2o	450

NECESSARY AMOUNT OF AIR

Alternator fan air flow	m³/s	2,71
-------------------------	------	------

STARTING SYSTEM

Auxiliary Voltage	Vdc	12
-------------------	-----	----

FUEL SYSTEM

Fuel Oil Specifications		LPG
Composition *		95% Propane
Fuel supply pressure	mbar	50 - 240
Fuel Tank	L	0



Gas ramp

- Manual shut-off valve
- Gas filter
- Double solenoid valve
- High pressure regulator
- Primary pressure regulator
- Low pressure switch
- High pressure switch
- Valve (tightness) testing system
- Inlet pressure manometer
- Outlet pressure manometer
- Special Start/Stop sequence